

Portable Pressure Steam Sterilizer

Characteristics:

- 1.Fully stainless steel structure.
- 2.Double scale indication pressure gauge.
- 3.Electric heated.
- 4.Easy to operate, safe and reliable.

Main Technical Parameters:

Model	Capacity	Working Pressure	Working Temperature	Max.Safety Pressure	Heat Average	Power	Packing Size	G.W/N.W
FSF-18LD	18L Φ280*260mm	0.14-0.16Mpa	126℃	0.165Mpa	≤ ± 0.1℃	2KW/ AC200V.50Hz	410*410*520mm	18kg/16kg
FSF-24LD	24L Φ280*390mm						410*410*630mm	19kg/17kg



Portable Pressure Steam Sterilizer

(Electric or LPG heated)

Characteristics:

- 1.Fully stainless steel structure.
- 2.Electric or LPG heated.
- 3.Double scale indication pressure gauge.
- 4.Easy to operate, safe and reliable.

Main Technical Parameters:

Model	Capacity	Working Pressure	Working Temperature	Max.Safety Pressure	Power	Packing Size(mm)	G.W/N.W
FSF-18LM	18L	0.14-0.16Mpa	126℃	0.165Mpa	AC220V.50Hz/2Kw	410*410*430	16/14KG
FSF-24LM	24L					410*410*550	17/15KG



Portable Pressure Steam Sterilizer

Characteristics:

- 1.Fully stainless steel structure.
- 2.Hand wheel type of quick-open door structure.
- 3.Indicator light indicates working state.
- 4.Double scale indication pressure gauge.
- 5.Time scope:0~60min.
- 6.Automatically shut off with beep reminding after sterilization.
- 7.Electric heated.
- 8.Easy to operate, safe and reliable.

Main Technical Parameters:

Model	Capacity	Working Pressure	Working Temperature	Temp. range	Max.Safety Pressure	Timer range	Heat average	Power	Packing Size(mm)	G.W/N.W
FSF-18LDJ	18L	0.14-0.16Mpa	126℃	126℃	0.165Mpa	0-60min	≤ ± 1℃	AC220V.50Hz/2Kw	410*410*430	16/14KG
FSF-24LDJ	24L								410*410*550	17/15KG

